

TOWN OF HILLSBOROUGH

STANDARD DETAILS

DIMENSIONS

- MINIMUM UNOBSTRUCTED WIDTH IS FOURTEEN FEET (14')
- EMERGENCY VEHICLES TURN-AROUND SHALL HAVE A MINIMUM 32' OUTSIDE RADIUS
- MINIMUM VERTICAL CLEARANCE IS 13.5 FEET
- MINIMUM RADIUS OF CURVATURE IS 30 FEET

GRADE

- MAXIMUM GRADE OF DRIVEWAY IS 16%, EXCEPT FOR THE FIRST 15 FEET BEHIND THE DRIVEWAY APPROACH WHICH IS LIMITED TO 5%

MISCELLANEOUS

- DRIVEWAY ENTRANCE TO STREET SHALL BE AS CLOSE TO 90 DEGREES AS AS POSSIBLE
- MINIMUM VERTICAL RADIUS OF CURVATURE AT GRADE CHANGES IS 50 FEET
- CROSS SLOPE OF DRIVEWAY SHALL BE 1% MINIMUM
- FINISHED SURFACE SHALL BE AN ALL WEATHER HARD SURFACE
- ROADBED PREPARATION, INCLUDING COMPACTION AND BASE MATERIAL, SHALL BE IN ACCORDANCE WITH SOILS REPORT RECOMMENDATIONS
- DRIVEWAYS AND BRIDGES SHALL BE DESIGNED TO SUPPORT A MINIMUM OF 40,000 POUNDS

DRIVEWAY STANDARDS

TOWN OF HILLSBOROUGH, 1600 Floribunda Ave. Hillsborough, CA. 94010
(650)375-7411

DATE: 06/13/04

SCALE: N.T.S.

ST 4.1