



STANDARD DETAILS

FOR THE TOWN OF HILLSBOROUGH

PUBLIC WORKS DEPARTMENT

ADOPTED: NOVEMBER, 2004

REVISION DATE: JANUARY 2011

Town of Hillsborough
1600 Floribunda Avenue
Hillsborough, CA 94010
(650)375-7444

TOWN OF HILLSBOROUGH STANDARD DETAILS

TABLE OF CONTENTS

	PAGES
1.0 WATER DETAILS	
⇒ WATER SERVICE	W 1.1
⇒ GATE VALVE ASSEMBLY	W 1.2
⇒ TEE & VALVE ASSEMBLY	W 1.3
⇒ TAPPING SLEEVE AND VALVE ASSEMBLY	W 1.4
⇒ FIRE HYDRANT ASSEMBLY	W 1.5
⇒ TAPPING SLEEVE, VALVE & FIRE HYDRANT ASSEMBLY	W 1.6
⇒ BLOW-OFF ASSEMBLY	W 1.7
⇒ AIR RELIEF VALVE	W 1.8
⇒ DEAD ENDING WATER MAINS	W 1.9
⇒ TRENCH BACKFILL & BEDDING - WATER MAIN	W 1.10
⇒ THRUST BLOCKS	W 1.11
⇒ WATER MAIN INSTALLATION	W 1.12
⇒ FABRICATED DOUBLE WATER MAIN OFFSET	W 1.13
⇒ TAPPING SLEEVE & VALVE	W 1.14
⇒ PRV ASSEMBLY	W 1.15
⇒ PRV MATERIALS LIST	W 1.16
2.0 SANITARY SEWER DETAILS	
⇒ SANITARY SEWER MANHOLE	SS 2.1
⇒ MAINLINE FRAME & COVER - MANHOLE, FLUSHING INLET	SS 2.2
⇒ SEWER LATERAL CLEANOUT	SS 2.3A
⇒ CLEANOUT BOX	SS 2.3B
⇒ ALTERNATE CLEANOUT	SS 2.3C
⇒ FLUSHING INLET	SS 2.4
⇒ LATERAL DETAIL	SS 2.5A
⇒ LATERAL CONNECTION TO EXISTING MAIN	SS 2.5B
⇒ TRENCH BACKFILL AND BEDDING	SS 2.6
⇒ OVERFLOW AND BACKFLOW DEVICES	SS 2.7
⇒ PIPE CROSSING REPAIR	SS 2.8
⇒ REINFORCED CONCRETE ENCASEMENT	SS 2.9
⇒ STANDARD SPECIFICATIONS - GENERAL NOTES	SS 2.10
⇒ STANDARD SPECIFICATIONS - PIPE AND FITTINGS	SS 2.11
⇒ STANDARD SPECIFICATIONS - PIPE AND FITTINGS (CONT'D.)	SS 2.11
⇒ STANDARD SPECIFICATIONS - TESTING REQUIREMENTS	SS 2.12 (1 of 2)
⇒ STANDARD SPECIFICATIONS - TESTING REQ'TS CONT'D	SS 2.12 (2 of 2)

TOWN OF HILLSBOROUGH STANDARD DETAILS

TABLE OF CONTENTS

	PAGES
3.0 STORM DRAIN DETAILS	
⇒ MANHOLE	SD 3.1
⇒ MANHOLE (FOR MAINS 45" TO 60" I.D.)	SD 3.2
⇒ CONCRETE CAP - FOR SHALLOW STORM DRAINS	SD 3.3
⇒ TRENCH BACKFILL & BEDDING	SD 3.4
⇒ CURB DRAIN	SD 3.5
⇒ INLET - TYPE GO	SD 3.6
⇒ TYPE GO APRON	SD 3.7
⇒ INLET - TYPE GOL	SD 3.8
⇒ TYPE GOL APRON	SD 3.9
⇒ STORM DRAIN INLETS - GENERAL NOTES	SD 3.10
4.0 STREET DETAILS	
⇒ DRIVEWAY STANDARDS	ST 4.1
⇒ REQUIREMENTS FOR PARKING STRIPS	ST 4.2
⇒ REQUIREMENTS FOR PARKING STRIPS Cont.	ST 4.2a
⇒ STREET SECTION - 40' RIGHT OF WAY	ST 4.3
⇒ STREET SECTION - 50' RIGHT OF WAY	ST 4.4
⇒ ROLL GUTTER - TYPE A (SLOPES 8% OR GREATER)	ST 4.5
⇒ ROLL GUTTER - TYPE B (SLOPES LESS THAN 8%)	ST 4.6
⇒ DRIVEWAY APPROACH	ST 4.7
⇒ VALLEY GUTTER	ST 4.8